



OPERATING INSTRUCTIONS - CL1200F

1. INSTALL REFLECTOR ("PHOTOGENIC" WITH QUICK CHANGE RING) BY SQUEEZING QUICK RELEASE TABS WHILE INSERTING TOP EDGE OF REFLECTOR QUICK RELEASE RING INTO QUICK CHANGE HOUSING.
2. INSTALL LAMP (400-1200 WATT TUNGSTEN-HALOGEN WITH G 9.5 MEDIUM 2 PIN BASE), FOLLOWING LAMP MANUFACTURER'S SAFETY & HANDLING INSTRUCTIONS. **DO NOT** TOUCH BULB WITH BARE FINGERS.
3. INSTALL SAFETY SHIELD. MAKE SURE THAT THE TWO (2) JUMPED PINS OF THE SAFETY SHIELD ALIGN WITH THE TWO (2) SAFETY SHIELD INTERLOCK SOCKETS ON THE LIGHT UNIT. THE FOCUS ADJUSTMENT SHOULD BE AT FULL SPOT. MAKE SURE THE SAFETY SHIELD PINS ARE FULLY SEATED IN THE INTERLOCK SOCKETS. THE LIGHT CAN NOT BE OPERATED WITHOUT THE SAFETY SHIELD PROPERLY INSTALLED.
4. MOUNT THE CLIP ON SCRIM ONTO REFLECTOR.

WARNING - SEVERE BURN HAZARD. THE SAFETY SHIELD OPERATES AT AN EXTREMELY HIGH TEMPERATURE. NEVER OPERATE THE LIGHT UNIT WITHOUT THE REFLECTOR AND CLIP ON SCRIM INSTALLED.

5. MOUNT THE LIGHT UNIT TO STAND OR WALL MOUNT. USE THE APPROPRIATE STAND ADAPTER BUSHING (SUPPLIED WITH THE LIGHT) FOR 1/2" OR 3/8" STAND TOPS. NO BUSHING IS REQUIRED WITH A 5/8" STAND TOP.
6. SWITCH LIGHT ON. USE THE FOCUS ADJUSTMENT KNOB TO GET DESIRED LIGHT BEAM COVERAGE.
7. REVERSE THE PROCEDURE OUTLINED IN ITEMS 1, 2, & 3 TO BREAK UNIT DOWN FOR STORAGE OR TRANSPORT. ALLOW FOR COOLING TIME OF AT LEAST 15 MINUTES.
8. USE ONLY WITH CIRCUIT BREAKER PROTECTED ELECTRICAL OUTLETS. IF CIRCUIT BREAKER TRIPS, CHECK FOR CIRCUIT OVERLOAD AND DISCONNECT OTHER ELECTRICAL EQUIPMENT AS NEEDED SO THAT THE TOTAL AMP DRAW ON THE CIRCUIT IS LOWER THAN THE RATING OF THE CIRCUIT BREAKER.

Photogenic Professional Lighting
525 McClurg Road
Youngstown, OH 44512
Telephone: 330-758-6658

ASSEMBLY & OPERATING INSTRUCTIONS - CL1200F



GENERAL HAZARD WARNING:

FAILURE TO COMPLY WITH THE PRECAUTIONS AND INSTRUCTIONS PROVIDED WITH THIS LIGHT UNIT CAN RESULT IN DEATH, SERIOUS BODILY INJURY, AND PROPERTY LOSS OR DAMAGE FROM HAZARDS OF FIRE, EXPLOSION, BURN, OR ELECTRICAL SHOCK.

ONLY PERSONS WHO CAN UNDERSTAND AND FOLLOW THE INSTRUCTIONS SHOULD USE THIS LIGHT UNIT.

THIS LIGHT UNIT IS DESIGNED FOR PROFESSIONAL USE ONLY. IT SHOULD NEVER BE USED FOR PURPOSES OTHER THAN PROFESSIONAL PHOTOGRAPHY.



WARNING:

NOT FOR HOME OR RECREATIONAL USE.



WARNING:

FIRE, BURN AND EXPLOSION HAZARD. KEEP COMBUSTIBLE MATERIALS SUCH AS PAPER, WOOD, OR CLOTH AT LEAST 6 FEET FROM THE FRONT AND AWAY FROM THE SIDES AND REAR OF THIS LIGHT. NEVER USE THIS LIGHT IN AREAS WHICH MAY CONTAIN VOLATILE OR AIRBORNE COMBUSTIBLES OR PRODUCTS SUCH AS GASOLINE, SOLVENT, PAINT THINNER OR UNKNOWN CHEMICALS.



WARNING:

ELECTRICAL SHOCK HAZARD.

DO NOT INSERT OBJECTS THROUGH THE FAN GRILL OR AROUND THE LAMP SOCKET. DO NOT PLACE THE LIGHT NEAR WET OR DAMP AREAS. THE CORD MUST BE UNPLUGGED WHEN CLEANING THE UNIT OR CHANGING THE LAMP.

SAFETY PRECAUTIONS:

1. CHECK THIS LIGHT UNIT AND SAFETY SHIELD THOROUGHLY FOR DAMAGE.
DO NOT OPERATE A DAMAGED LIGHT UNIT OR USE WITH A DAMAGED SAFETY SHIELD
2. **DO NOT** MODIFY THIS LIGHT UNIT OR OPERATE A LIGHT UNIT THAT HAS BEEN MODIFIED FROM ITS ORIGINAL CONDITION.
3. OPERATE ONLY ON A STABLE, LEVEL SURFACE.
4. AVOID LOOKING DIRECTLY INTO THE LIGHT.
5. USE CAUTION WHEN MAKING LIGHT ADJUSTMENTS. THE LIGHT CAN DEVELOP VERY HOT SURFACES, PARTICULARLY ON THOSE SURFACES CLOSEST TO THE LAMP.
6. NEVER OPERATE THE LIGHT WITHOUT A REFLECTOR. THE REFLECTOR MUST BE LARGE ENOUGH SO THAT THE SAFETY SHIELD IS INACCESSIBLE FROM THE SIDES.
7. ALLOW THE LIGHT UNIT TO COOL FOR AT LEAST 15 MINUTES AFTER IT IS SWITCHED OFF BEFORE HANDLING FOR ANY REASON
8. ALWAYS UNPLUG THE LIGHT IF IT IS NOT BEING USED.
9. SECURE POWER CORD SUCH THAT THE LIGHT CANNOT BE PULLED OVER BY THE CORD.
10. DO NOT USE AN EXTENSION CORD UNLESS IT IS RATED FOR 10 AMPS OR MORE AND NO. 14 AWG MINIMUM WIRE SIZE.
11. IF PLUG GETS HOT, CHECK CONDITION OF WALL OUTLET.
12. NEVER OPERATE THE LIGHT UNIT IF THE COOLING FAN BLADES ARE NOT RUNNING.
13. SWITCH THE LIGHT UNIT OFF IMMEDIATELY IF SMOKE OR FUMES ARE DETECTED. CHECK LAMP AND MAKE SURE IT HAS BEEN CLEANED PER THE LAMP MANUFACTURER'S INSTRUCTIONS.

015943-00 (REV1)

NOTES:

- 1) TEXT AND GRAPHICS COLOR: BLACK
- 2) BACK GROUND COLOR: WHITE
- 3) TO BE PRINTED ON 8 1/2" X 11" SHEETS; DOUBLE SIDED; SUCH THAT PRINTING IS NOT VISIBLE FROM THE REVERSE SIDE.

Photogenic
Professional Lighting
525 McClurg Rd. - Youngstown, OH 44512

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
UNLESS OTHERWISE SPECIFIED
FRACTIONS ARE
IN INCHES
SERIAL ALL SHARP EDGES

FORM	DATE	11-22-99	DO NOT SCALE PRINT
TRND	DATE	11-22-99	
APPRD	DATE		
FIRST USED ON	CL1200F	REV 1 OF 1	
FORM REV	CL1200FSC	SCALE	FULL
MATERIAL	SEE NOTES		
TITLE	INSTRUCTION SHEET CL1200FSC		
C PART NO:	015943-00	REV	1